







Smart, inspiring hood lighting

Our 300 LEDlights Hood requires far less energy than other lights and has a much longer life expectancy. Efficient and helpful, these lights ensure exceptional visibility for all your demands while cooking.

Our oven hood fits discreetly into the cabinet above, leaving you with more room to cook. It smoothly opens to activate the extractor fan, and can be pushed back into place when finshed. Combine better performance with a sleek design for more efficient mealtimes.

Product Benefits & Features



Long life and great lighting – let LEDlights lead the way

Enjoy expert illumination while you cook. Our LEDlights use far less energy than other lights and provide excellent visibility in the kitchen, ensuring you cook with greater confidence and agility.



Reliably reduces cooking fumes

Create a cleaner atmosphere for you to cook, eat and relax in with this efficient cooker hood. Its reliable motor effectively reduces cooking fumes so you can enjoy your time in the kitchen more than ever.

Standard grease filter for a clean kitchen

Our reliable grease filter means you can always enjoy a clear cooking space. When a new filter is required, it can be easily washed or replaced. Your kitchen will be cleaner for longer.



Mechanical Controls - hood settings made simple

Your cooker hood functions can be easily reached with our Mechanical Controls. Adjust the light settings or the fan speed for fast, flexible cooking.

- · Operation via sliding switch
- Recirculation or extraction options
- Noise level: dB(A)



LFE216S

Product Specification	
Colour	Grey
No. of speed settings	3; Micro switch
Type of Controls	Mechanical slider
Lamp type	LED bulb
Energy class	D
Hoods_Capacity_Min_Max_Intensive_m3h	110/284/-
Hoods_Noiselevel_Min_Max_Intensiv e_dB	47/67/-
Grease filter efficiency class	В
Minimum distance from cooking top	50
Minimum distance from cooking top	70
Energy consumption per year (kWh)	66.1
Size	60
Recirculatory	Yes
External evacuation	Yes
LightTemperature	3000
No. of lamps	2
Connection to hob (H2H)	No
Fluid dynamic efficiency class	E
Lighting efficiency class	Α
Recirculation min, m3/h	90
Recirculation max, m3/h	133
Recirc sound power min, dB(A)	60
Recirc sound power max, dB(A)	71

PNC	942 150 790
EAN number	7332543614219
Net Weight	9.3
Gross weight (kg)	10.5
Dimensions HxWxD in mm	400x598x270
Installation	Integrated
Grease filters	1

