

N 50, wall-mounted cooker hood, 90 cm, Stainless steel  
D94BHM1NOB



COOKING PASSION SINCE 1877



B



The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ CleanAir Recirculation Filter (separate accessory): nothing but clean air thanks to the premium recirculation filter with high odour reduction (ca. 95%). Regenerative filter also available.
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.

#### Features

##### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 583-912/583-1022  
 Height of product, without chimney (mm) : 53  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 12.777  
 Type of control : Electronic  
 Maximum output air extraction (m<sup>3</sup>/h) : 372  
 Boost position output recirculating (m<sup>3</sup>/h) : 360  
 Maximum output recirculating air (m<sup>3</sup>/h) : 290  
 Boost position air extraction (m<sup>3</sup>/h) : 604  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 60  
 Diameter of air outlet (mm) : 120 / 150  
 Grease filter material : Washable aluminium  
 EAN code : 4242004224174  
 Connection Rating (W) : 220  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation typology : Wall-mounted

#### Optional accessories

|           |  |
|-----------|--|
| Z50XP0X0  | CleanAir act.carbon filter regenerative  |
| Z5170X1   | CleanAir active carbon filter spare part |
| Z51DXA0X0 | Active carbon filter                     |
| Z51DXU0X0 | Recirculating kit                        |
| Z51FXI0X0 | Integrated CleanAir Recirculation Kit    |
| Z51FXJ0X0 | Integrated CleanAir Recirculation Kit    |
| Z5270X0   | CleanAir Recirculation Kit               |
| Z5895N0   | Stainless steel back panel               |
| Z5905N0   | Chimney extension 1000 mm                |
| Z5915N0   | Chimney extension 1500 mm                |



N 50, wall-mounted cooker hood, 90 cm, Stainless steel  
D94BHM1NOB

## Features

### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)\*
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 372 m<sup>3</sup>/h  
Intensive 604 m<sup>3</sup>/h
- Noise max. Normal Level: 60 dB\*

### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- For wall mounted installation

### Design

- Stainless steel
- Box design
- Chimney hood
- Touch control
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 372 m<sup>3</sup>/h  
Intensive 604 m<sup>3</sup>/h
- Max. extraction rate: 604 m<sup>3</sup>/h
- Extraction rate in recirculation mode:  
Max. normal use: 290 m<sup>3</sup>/h  
Intensive: 360 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)  
Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- Noise max. Normal Level: 60 dB\*
- Noise levels in recirculation mode:  
Max. normal use: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)  
Intensive: 75 dB(A) re 1 pW (62 dB(A) re 20 µPa sound pressure)
- 
- Light Intensity: 214 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 48.5 kWh/year\*

### Optional accessories

- Recirculating kit Z5270X0

\* In accordance with the EU-Regulation No 65/2014

