



### Clean lines, clean air

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

## Product Benefits & Features

### The hands-free hood

This cooker hood has Hob2Hood, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself, there are manual controls



- Washable aluminium grease filters
- Extraction mode
- Maximum recirculation rate of 220 m<sup>3</sup>/h
- 65 dB(A) noise level
- Recirculation or extraction options
- For wall mounting between furniture or as a stand alone unit

### Natural air, effortlessly and silently.

The sleekly designed AEG hood removes lingering odours quietly thanks to a super quiet breeze technology. So you can have a better environment in your kitchen effortlessly and silently.



### Benefit from long-lasting lighting

Gain the benefits of LED lighting. Clear and bright, it makes ideal task lighting over a hob and, additionally, it's long-lasting and energy-efficient too.



### Clean air with less energy

A strong motor with low-energy consumption means this hood is reliable and efficiently clears away kitchen odours.

### All cooking vapours removed – in silence

Thanks to innovative technology, this hood clears your kitchen of unwanted cooking vapours almost unnoticeably. What's more, the cooker hood's virtually silent operation helps you create the perfect atmosphere in your home.

#### Product Specification

Installation	Chimney	No. of lamps	2
Size	90	Grease filters	3
Dimensions, HxWxD	759-1204x898x455	Recirc sound power min, dB(A)	55
Minimum distance from cooking top	50	Recirc sound power max, dB(A)	66
Minimum distance from cooking top	65	Recirculation min, m3/h	250
Cord Length	1.3	Recirculation max, m3/h	380
Voltage	220-240		
Required Fuse	No		
Frequency	50		
Colour	Stainless steel		
Charcoal filter type	MCFB58		
Superperforming charcoal filter compatible	MCFB66, 902 980 215		
Energy class	A		
Fluid dynamic efficiency class	A		
Lighting efficiency class	A		
Grease filter efficiency class	B		
Capacity minimum, m3/h	285		
Capacity, Max m³/h	400		
Capacity intensive, m3/h	700		
Sound power min speed, dB(A)	44		
Sound power max speed, dB(A)	54		
Sound power intensive, dB(A)	65		
No. of speed settings	3+Intensive, Breeze function		
Lamp type	LED spotlight		

